

屋内消火栓 配管摩擦損失水頭 m/100m

(JIS-G3452)

流量	呼び	32mm	40mm	50mm	65mm	80mm	90mm	100mm	125mm	150mm
60L/min		4.756	2.258	0.701	0.208	0.090	0.044	0.025	0.009	0.004
70L/min		6.326	3.004	0.932	0.277	0.120	0.059	0.033	0.012	0.005
80L/min		8.099	3.846	1.194	0.354	0.153	0.076	0.042	0.015	0.007
90L/min		10.071	4.782	1.484	0.44	0.19	0.095	0.052	0.019	0.008
120L/min		17.146	8.141	2.526	0.749	0.323	0.160	0.088	0.031	0.013
130L/min		19.883	9.440	2.929	0.869	0.375	0.186	0.103	0.036	0.016
140L/min		22.805	10.828	3.360	0.997	0.430	0.213	0.118	0.041	0.018
150L/min		25.910	12.300	3.820	1.130	0.490	0.240	0.130	0.050	0.020
160L/min		29.196	13.862	4.302	1.276	0.55	0.273	0.151	0.053	0.023
180L/min		36.303	17.237	5.349	1.586	0.684	0.34	0.188	0.066	0.029
190L/min		40.122	19.050	5.911	1.753	0.756	0.375	0.206	0.072	0.031
260L/min		49.777	34.033	10.560	3.131	1.350	0.670	0.370	0.129	0.056
300L/min		93.400	44.350	13.760	4.080	1.760	0.870	0.480	0.170	0.070

(JIS-G3454スケジューラ40)

流量	呼び	32mm	40mm	50mm	65mm	80mm	90mm	100mm	125mm	150mm
60L/min		4.888	2.367	0.714	0.240	0.105	0.052	0.028	0.010	0.004
70L/min		6.502	3.149	0.950	0.320	0.140	0.069	0.038	0.014	0.006
80L/min		8.324	4.031	1.216	0.41	0.179	0.089	0.049	0.018	0.008
90L/min		10.35	5.012	1.512	0.509	0.223	0.111	0.06	0.022	0.009
120L/min		17.622	8.533	2.573	0.866	0.379	0.188	0.102	0.036	0.015
130L/min		20.435	9.895	2.984	1.005	0.439	0.218	0.118	0.042	0.018
140L/min		23.437	11.350	3.423	1.153	0.504	0.250	0.136	0.048	0.021
150L/min		26.630	12.890	3.890	1.310	0.570	0.280	0.150	0.050	0.020
160L/min		30.005	14.53	4.382	1.476	0.646	0.32	0.174	0.062	0.027
180L/min		37.31	18.067	5.448	1.835	0.803	0.398	0.216	0.077	0.033
190L/min		41.235	19.968	6.021	2.027	0.886	0.440	0.238	0.084	0.036
260L/min		73.666	35.672	10.756	3.622	1.584	0.785	0.425	0.151	0.064
300L/min		95.990	46.480	14.020	4.720	2.060	1.020	0.550	0.200	0.080

連結送水管 配管摩擦損失水頭 m/100m

(JIS-G3452)

流量	呼び	65mm	80mm	90mm	100mm	125mm	150mm	200mm
200L/min		1.93	0.83	0.41	0.23	0.08	0.03	0.01
400L/min		6.95	3.00	1.49	0.82	0.29	0.12	0.03
600L/min		14.71	6.34	3.15	1.74	0.60	0.26	0.07
800L/min		25.04	10.80	5.36	2.96	1.03	0.45	0.12
1600L/min		90.28	38.93	19.31	10.66	3.71	1.61	0.42
2400L/min		191.15	82.43	40.88	22.56	7.85	3.41	0.89
3200L/min		325.46	140.36	69.61	38.41	13.36	5.81	1.51

(JIS-G3454スケジューラ40)

流量	呼び	65mm	80mm	90mm	100mm	125mm	150mm	200mm
200L/min		2.23	0.97	0.48	0.26	0.09	0.04	0.01
400L/min		8.04	3.51	1.74	0.94	0.33	0.14	0.04
600L/min		17.01	7.44	3.69	2.00	0.71	0.30	0.08
800L/min		28.97	12.67	6.28	3.40	1.21	0.51	0.13
1600L/min		104.43	45.67	22.68	12.27	4.34	1.84	0.47
2400L/min		221.11	96.69	47.94	25.97	9.20	3.90	0.99
3200L/min		376.48	164.63	81.63	44.22	15.66	6.64	1.69

屋外消火栓 配管の摩擦損失水頭 m/100m

(JIS-G3452)

流量	呼び	65mm	80mm	100mm	125mm	150mm
350L/min		5.43	2.34	0.64	0.22	0.10
400L/min		6.95	3.00	0.82	0.29	0.12
700L/min		19.56	8.44	2.31	0.80	0.35
800L/min		25.04	10.80	2.96	1.03	0.45

(JIS-スケジューラ40)

流量	呼び	65mm	80mm	100mm	125mm	150mm
350L/min		6.28	2.74	0.74	0.26	0.11
400L/min		8.04	3.51	0.94	0.33	0.14
700L/min		22.63	9.89	2.68	0.94	0.40
800L/min		28.97	12.67	3.40	1.21	0.51

※寸法・仕様等は、予告なく変更することがあります。 ※Dimensions, Specifications, etc. are subject to change without notice.